

AQ-3000

Features

Aqua Phase Model AQ-3000 is the work horse of the Aqua Phase line. AQ-3000 is designed and built to handle the heavy washing requirements of large long term care facilities, large home medical and durable medical equipment dealers, and hospitals.

The AQ-3000 with the Disinfection Application System will be an integral part of your infection control protocols. Some units of Model AQ-3000 have had tens of thousands of cycles ran through them and are still going strong. AQ-3000 features double wall Stainless Steel construction to act as a heat insulator. The AQ-3000 is mounted on four large, durable casters to allow for easy relocation and The AQ-3000 comes standard with the Disinfection Application System, the Wheel Rotation System for wheelchair wheels and Safety Glass Window.

One of the key additional standard features of the AQ-3000 is the wall mounted studs. This allows you, now or in the future, to order the Utility Wash Trays System. More importantly, it allows you to customize your own racking system to handle your specific wash needs.

Standard Features - AQ-3000:

- Stainless Steel Construction and Spray Arms
- Double Walled
- Disinfectant Application System
- Front Door Safety Glass Window
- Variable Wash Time Cycles (3, 5, or 7 minute)
- Rinse Cycle System
- Rotation of Wheelchair Wheels (Front & Rear)
- Heavy Duty Casters
- Hot Water Hose Set (Set of 2 – 3m)

Options – AQ-3000:

- Equipment Loading Wash Rack
- Utility Wash Trays
- Electronic Temperature Monitor
- Lighted Wash Chamber
- Air Dry Blower
- Utility Chamber Floor
- Multi-Size Wheel Rotator
- Special Time Cycles
- 220 Volt 50/60 Hz Operation
- Long Hot Water Hose Set (Set of 2 – 7.5m)

Design Features - AQ-3000:

Construction (Stainless Steel)	Double Walled
System Controls Are By	Logic Controller
Spray Arm Assemblies	Stainless Steel
Tested to European Specs.	Yes
UL Listed Electronics Assembly	Standard
Rinse Cycle	Standard
Cleaner Injection System	Peristaltic
Wash Cycle Lengths	3,5 or 7 minutes
Disinfectant Application (Optional)	Automatic
Filter Clogging Signal	Standard
Water Level Sensor	Electronic
GFCI Breaker in Power Cord	Standard
Safety Switch Front & Rear	Standard
Maximum AMP Draw	12.6
Warranty - Wash Chamber	5 Years
Warranty – Parts	1 Year
Warranty – Labor	90 Days

Dimensions - AQ-3000:

Machine Outside Width	860 mm
Machine Outside Length	1676 mm
Machine Outside Height	1600 mm
Wash Chamber Width	673 mm
Wash Chamber Height	1300 mm
Wash Chamber Length	990 mm
Shipping Weight	545 kg



Aqua Phase

PO BOX 3514, RUNDLE MALL SA 5000

PHONE: +61 8 7200 4226 FAX: +61 8 8121 7668 MOBILE: +61 419 296 694
EMAIL: sales@aquaphase.com.au WEB: www.aquaphase.com.au